


# Announcing the **NEW** ZP Express Program



Receive our most popular ZP temperature and/or humidity chambers in just 2-4 weeks. You can even select from common options listed below.

## Applicable Models

<b>Single Stage: -34°C to +190°C</b> 208/230V, 1/3 Ph, 60 Hz.	<b>Cascade: -70°C to +190°C</b> 208/230V, 1/3 Ph, 60 Hz.	<b>Tundra: -45°C to +190°C</b> 208/230V, 3 Ph, 60 Hz.
<b>Temperature Chambers</b> ZPE-8-2-H/AC ZPE-16-2-H/AC ZPE-32-2-H/AC	<b>Temperature Chambers</b> ZPE-8-2-2-H/AC ZPE-16-2-2-H/AC ZPE-32-2-2-H/AC	<b>Temperature Chambers</b> ZPE-8-3.5-SCT/AC ZPE-16-3.5-SCT/AC ZPE-32-3.5-SCT/AC
<b>Temperature/Humidity Chambers</b> ZPHE-8-2-H/AC ZPHE-16-2-H/AC ZPHE-32-2-H/AC	<b>Temperature/Humidity Chambers</b> ZPHE-8-2-2-H/AC ZPHE-16-2-2-H/AC ZPHE-32-2-2-H/AC	<b>Temperature/Humidity Chambers</b> ZPHE-8-3.5-SCT/AC ZPHE-16-3.5-SCT/AC ZPHE-32-3.5-SCT/AC

## Options Available

- |                              |                            |
|------------------------------|----------------------------|
| • Customer event             | • Low humidity             |
| • Digital Input/output       | • Dry air purge system     |
| • Recirculating water option | • LN2 boost                |
| • Demineralizer cartridge    | • Water pressure regulator |
| • Rear top vent exhaust      | • Reverse osmosis          |
| • Sound deadening            | • EZ-View                  |
| • Shelves                    | • Extended warranty        |



## Notes:

Shipping 2-4 weeks from order acknowledgment  
 Please consult factory for quantity orders of the same model  
 Not applicable to 50 Hz. Models

Weiss Technik North America, Inc.  
 Cincinnati Facility  
 12011 Mosteller Road  
 Cincinnati, OH 45241  
 (p) 513-326-5252  
 (f) 513-326-5258  
[www.cszindustrial.com](http://www.cszindustrial.com)

**CSZ**  
**Cincinnati Sub-Zero**  
**The Testing Standard.**